

BAGRAM (OAIX)

✚ IFR TAKE-OFF MINIMUMS AND DEPARTURE PROCEDURES

Civil Airports and Selected Military Airports

CIVIL USERS: Title 14 Code of Federal Regulations Part 91 prescribes take-off rules and establishes take-off minimums for certain operators as follows: (1) Aircraft having two engines or less - one statute mile. (2) Aircraft having more than two engines - one-half statute mile.

Airports with IFR take-off minimums other than standard are listed below. Departure procedures and/or ceiling visibility minimums are established to assist all pilots conducting IFR flight in avoiding obstacles during climb to the minimum enroute altitude. Take-off minimums and departures apply to all runways unless otherwise specified. Altitudes, unless otherwise indicated, are minimum altitudes in feet MSL.

MILITARY USERS: Special IFR departure procedures not published as Standard Instrument Departure (SIDs) and civil take-off minima are included below and are established to assist pilots in obstacle avoidance. Refer to appropriate service directives for take-off minimums.

AIRPORT NAME	TAKE-OFF MINIMUMS
--------------	-------------------

BAGRAM (OAIX) 09239	
----------------------------	--

Bagram, Afghanistan

Diverse departure not authorized.

TAKE-OFF MINIMUMS: Rwy 03: 3900-4800m for climb in visual conditions. Rwy 21: 3900-4800m for climb in visual conditions.

DEPARTURE PROCEDURE: Rwy 03: Use appropriate SID/ODP or for climb in visual conditions within 7.46 NM of OAIX. Cross OAIX at or above 8600' then proceed via BGM R-204 to CAMUX (BGM 13 DME). At CAMUX, turn left and intercept OKB TACAN R-339 direct to OKB. Depart OKB R-195 to DOMDE (OKB 10 DME). Cross DOMDE at or above 14,500'. Expect published holding: Hold South of DOMDE, 015° inbound, 11 NM, right turns. Minimum holding altitude 14,500'. Maximum holding altitude FL180. **Rwy 21:** Use appropriate SID/ODP or for climb in visual conditions within 7.39 NM of OAIX. Cross OAIX at or above 8600' then proceed via BGM R-204 to CAMUX (BGM 13 DME). At CAMUX, turn left and intercept OKB TACAN R-339 direct to OKB. Depart OKB R-195 to DOMDE (OKB 10 DME). Cross DOMDE at or above 14,500'. Expect published holding: Hold South of DOMDE, 015° inbound, 11 NM, right turns. Minimum holding altitude 14,500' and maximum holding altitude FL180.

TAKE-OFF OBSTACLES: Rwy 03: 4883' MSL tower, 1184' after DER, 682' left of centerline. **Rwy 21:** 4992' MSL tower, 1822' after DER, 823' left of centerline, 4984' MSL tower, 1626' prior to DER, 778' left of centerline, 4873' MSL terrain, 25' from DER, 499' right of centerline, 4872' MSL terrain, 63' after DER, 515' right of centerline, 4872' MSL terrain, 89' after DER, 522' right of centerline, 4872' MSL terrain, 90' after DER, 499' right of centerline, 4872' MSL terrain, 156' after DER, 499' right of centerline. 4869' MSL terrain, 6' from DER, 378' right of centerline, 4784' MSL terrain, 0' from DER, 484' right of centerline.